

Chain Drive | Augers



Selecting the right auger for your compact excavator can be tricky; you'll need to consider not only the hydraulic flow, but the pressure too; soil conditions and hole size will play a role as well. CEA has the expertise to help you select the correct auger drive to fit your needs. The full auger line available is sure to provide correct mounting pins, hydraulic-powered auger drive unit, auger drilling bit and specialized wear parts.



Chain auger drives feature pre-stressed, fully adjustable reduction drives and the strongest connecting links available. Come with hoses, top link and flat face couplers. Mounts are sold separately. All bits sold separately.

- ⊙ **CAPABLE OF DIGGING HOLES UP TO 48" IN DIAMETER**
- ⊙ **HIGH TORQUE CHAIN-REDUCTION DRIVE**
- ⊙ **MOUNTING ENSURES PERFECT BALANCE OF AUGER**
- ⊙ **AVAILABLE WITH 2-9/16" ROUND, AND 2" HEX OUTPUT SHAFTS**

SPECIFICATIONS

Model	Weight (lbs/kg)	Hyd. Req. (gpm/lpm)	Max. Auger Dia. (in/mm)	Speed (rpm)	Theo. Torque (lbs. ft/Nm)
500XL	133/60.3	6-14/23-53	18/457	132 @ 14 gpm	980/882 @ 3000 psi
750CL	190/86.2	8-20/30-76	24/610	161 @ 20 gpm	1118/1003 @ 3000 psi
1200CL	228/103.4	10-20/38-76	30/762	106 @ 20 gpm	1724/1547 @ 3000 psi
1650CL	243/110.2	14-24/53-91	36/914	88 @ 24 gpm	2478/2213 @ 3000 psi
2175CL	445/201.9	18-24/68-91	48/1219	73 @ 24 gpm	2989/2703 @ 3000 psi