



Break concrete quickly and easily into load-ready debris. Only two moving parts provide enough power to break through the toughest materials. CEA has models available from the 150 ft/lb impact energy class to 1,500 ft/lb impact energy class.



Mounting brackets are available for most compact excavators, and breakers come with amoil point tool. Hoses not included.

*When ordering breakers for excavators equipped with quick attach, customer must specify type of quick attach.*

- ⊙ **NO BACK HEAD CHARGING REQUIRED**
- ⊙ **“CD” SIDE BOLT DESIGN MEANS LESS THROUGH BOLT FAILURE**
- ⊙ **EASY TO INSTALL WORKING STEEL**

## SPECIFICATIONS

Model	Weight (lbs/kg)	Hyd. Req. (gpm/lpm)	Impact Energy Class (lb-ft/J)	Cycles/Blows per Minute
EB15	165/74.8	3-5/12-20	150/203	900-1200
EB25	225/102.1	4-8/16-30	250/339	900-1200
EB35	560/254.0	6.5-10.5/25-40	350/475	700-900
EB50	780/353.8	8.5-13/32-49	500/678	750-1000
EB75	575/260.8	11-16/42-61	750/1017	700-900
EB100	950/430.9	13-40/49-151	1000/1356	650-1500
EB150	1100/499.0	17-30/65-114	1500/2034	550-900