



Four rows of 104 staggered teeth for efficient mulching.

The standard flow EDGE Brush Mulcher attachment is designed for efficient mulching of brush in land clearing applications on standard-flow hydraulics.

This powerful machine is equipped with a safety pusher bar to push brush or small trees down and allow the mulcher teeth to contact the lower portion of the brush to mulch it up to 1" below grade. The rest of the plant is mulched as the machine moves through the working area.

Features include 104 carbide-tipped teeth for long tooth life, smooth operations and fine mulch. The rotor is designed with 4 staggered rows of teeth around the circumference that cut into and mulch wood material as it moves into the rotor. It also features a rear chain shield and a pressure gauge on the back of the mulcher for the operator to monitor hydraulic pressure while operating. A relief valve in the hydraulic circuit is also featured to prevent overloading of any drive components. Comes complete with hoses and flat face couplers.



Pressure gauge on back to monitor hydraulic pressure while operating.

- ⊙ POWERFUL BRUSH MULCHING ON STANDARD-FLOW HYDRAULICS
- ⊙ 104 CARBIDE-TIPPED TEETH FOR LONG TOOTH LIFE AND FINE MULCH
- ⊙ SAFETY PUSHER BAR TO PUSH BRUSH OR TREES DOWN INTO THE MULCHER
- ⊙ 4 STAGGERED ROWS OF TEETH FOR EFFICIENT MULCHING
- ⊙ PRESSURE GAUGE TO MONITOR HYDRAULIC PRESSURE DURING OPERATION
- ⊙ RELIEF VALVE IN HYDRAULIC CIRCUIT PREVENTS OVERLOAD OF DRIVE COMPONENTS

SPECIFICATIONS

| Model | Weight (lbs) | Hyd. Req. (gpm/lpm) | No. of Teeth | Digging Depth (in/mm) | Working Width (in/mm) | Overall Width (in/mm) |
|-------|--------------|---------------------|--------------|-----------------------|-----------------------|-----------------------|
| M48SF | 1425.0 | 16-21/61-80 | 104 | 1/25 | 48/1219 | 62/1575 |