



An efficient and precise attachment that makes road cuts as well as it make utility cuts. The rock wheel cuts widths of 2.5" to 4.5" (633 mm to 114 mm) and depths of up to 24" (610 mm). Rock wheels require dual circuit hydraulics. Each Rock Wheel will include mount and hoses - Couplers NOT included. This is a high-flow attachment ONLY.

- ⊙ REPLACE SAW CUTTING AND TRENCHING FOR ONE PASS UTILITY WORK
- ⊙ USE FOR PATCH CUTS, ROADWAY EXPANSION AND UTILITY WORK
- ⊙ HEAVY-DUTY PLANETARY GEARBOX

SPECIFICATIONS

Model	Weight (lbs/kg)	Hyd. Req. (gpm/lpm)	Speed (rpm)	No. of Teeth	Depth (in/mm)	Working Width (in/mm)	Productivity (ft/m per minute)
RW18-2	1800.0/816.5	26/98	60	42	18/457	2.5/64	(up to) 15/4.6
RW18-4	1800.0/816.5			44		4.5/114	(up to) 15/4.6
RW24-2	2100.0/952.6	30/114		56	24/610	2.5/64	(up to) 15/4.6
RW24-4	2545.0/1154.4			66		4.5/114	(up to) 15/4.6